Product information

Motorbike Speed Shooter

PI 41/06/13/2024



Modern ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- good corrosion protection
- residue-free combustion
- guarantees optimum combustion
- improves acceleration
- removes deposits from entire fuel system
- highly economical
- prevents carburetor icing
- higher performance gain

Technical data

Base Additive mixture in carrier fluid

Color/appearance light brown Density at 15 °C $0,825 \text{ g/cm}^3$ Flash point >63 °C

Odor characteristic

Form liquid Viscosity at 40 °C <7 mm²/s

Areas of application

For 2-stroke and 4-stroke gasoline engines (carburetor and injection).

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline fuel grades. 80 ml is sufficient for up to 10 l of fuel.

Available pack sizes

80 ml Can sheet metal 7820

GB

80 ml Can sheet metal 7823

TR

80 ml Can sheet metal 7915

VN

80 ml Can sheet metal 8265

JΡ



Available pack sizes

80 ml Can sheet metal 20585

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de